




您必须了解的 USB3.1 与 Type C

叶树栋
市场开发经理
186 1216 0975
sandro_je@keysight.com

2016年3月



USB接口应用



Topics Today



- **TYPE-C 接口技术**

- TYPE-C 接口
- TYPE-C 技术
- Power Delivery 技术
- 问题和挑战

- **TYPE-C 测试方案**

- 发送端测试
- 接收端测试
- Cable/连接器测试
- Power Delivery测试

Keysight 数字总线标准专家组

Industry's most comprehensive application-specific measurements


Keysight experts helping define next generation standards, and solutions

Memory Perry Keller	DisplayPort Brian Fetz	USB Jit Lim	Computer Rick Eads	Optical Greg LeCheminant	HDMI Stefan Friebe	Storage Matthew Woerner	MIPI Roland Scherzinger
Board of Directors JEDEC	Board of Directors VESA	Contributor USB-IF Thunderbolt	Contributor, Board Member Alumni PCI-SIG	Contributor IEEE, OIF-CEI, T11 FC	Contributor HDMI BoD (Thomas Dippon)	Contributor SATA-IO, T10 SAS	TSG Member UniPro Vice Chair MIPI Alliance
Compliance Chair UFSA	Contributor VESA Phy Sub Group USB-IF Compliance						

LPDDR4, UFS	DP 1.3 Type-C	USB 1/2/3.x Type-C	PCIe G3, G4, PAM4 (RT)	PAM-4, CEI 3.1	HDMI 2.0	SATA, SAS-3	D/M/C-PHY, UniPro
--------------------	----------------------	---------------------------	-------------------------------	-----------------------	-----------------	--------------------	--------------------------



Keysight 对全球USB认证测试实验室的支持



***Test Labs Currently Qualified for USB 3.0 Certification**
Approved labs are listed at <http://www.usb.org/developers/compliance/labs>

Topics Today



- **TYPE-C 接口技术**


- TYPE-C 接口
- TYPE-C 技术
- Power Delivery 技术
- 问题和挑战

- **TYPE-C 测试方案**

- 发送端测试
- 接收端测试
- Cable/连接器测试
- Power Delivery测试

Type C Connector

Big Discontinuity



Type A



12mmx4.6mm

Type B



13.35mmx2.4mm

Type C




8.3mmx2.5mm

Industry Drivers for Type C

- ★ ***Eliminate form factor orientation dependency***
- ★ ***Enables infrastructure for adoption by other standards (i.e. video)***
- ★ ***Establishes power delivery and charging infrastructure***



USB Type C-Signal Pins




USB Type C Test Implications

Type C Pin	Feature	Test Implication Comment
USB2 pins D+, D-	USB2 is assumed to be active in type C designs.	USB2 Host/Device testing required.
Config pins CC1, CC2	Three functions: -Termination/Orientation detection -Vconn Supply -Power Delivery Channel	PD channel testing (protocol, PD channel phy) V_{Conn} loading. Must be terminated properly depending on DUT type. Must be controlled to test both ports (TX/RX 1&2) of the interface during USB3.x testing). Channel used to set up alternate modes.
SBU1, SBU2	Control of alt standards. (TBT, DP, MHL)	Used to control devices in alternate modes
Power V_{Bus} , Ground	Voltage Range: 5 to 20 volt Current Range: 0 to 5 amp Direction: provider or consumer, or both.	Wide range of operation possible on any given device. Verification of V/I profile. Test system be designed for setting up arbitrary Vbus state, or, several, or only one Vbus state.
TX1, TX2, RX1, RX2	High Speed differential lanes	USB3.1 uses only 1 port (TX/RX set) at a time and will require testing the flipped condition. TBT devices will use both ports. DP may have all four lanes as either TX or RX lanes depending on the device.

Alternate Mode


A port could wake up as USB 3.1, then get configured to DisplayPort 1.3



Alternate Mode


- An operational mode of devices on a link that dynamically reassigns USB Type-C pin functionality by communication via the Power Delivery channel to change the character of the link.

Example: a 'device' can wake up USB3.1 and change to DP1.3




DisplayPort 1.3, & MHL, & Thunderbolt

Power Delivery 2.0




Power Delivery 2.0 Application




USB Power Delivery Technologies

- Management of a power network and device modes through a one line interface. The interface can set up the network to quickly charge devices with up to 5 amps, supply power to active cables, discover cable functionality, enable guest protocols (Alternate Modes), facilitate device role and power direction swaps.
- Power Management



- V_{Conn} Power Management




USB Type C Power Options

Precedence	Mode of Operation	Nominal Voltage	Maximum Current
Highest ↓ Lowest	USB PD	Configurable	5 A
	USB Type-C Current @ 3.0 A	5 V	3.0 A
	USB Type-C Current @ 1.5 A	5 V	1.5 A
	USB BC 1.2	5 V	Up to 1.5 A
	Default USB Power	USB 3.1	5 V
USB 2.0		5 V	500 mA

- PROFILE 1**
5V @ 2A
10W
Default
- PROFILE 2**
5V @ 2A, 12V @ 1.5A
18W
- PROFILE 3**
5V @ 2A, 12V @ 3A
36W
- PROFILE 4**
5V @ 2A, 12V, 20V @ 3A
60W
Limit fo
- PROFILE 5**
5V @ 2A, 12V, 20V @ 5A
100W
Limit fo


Sink/source can be swapped, power direction no longer fixed



The Key to the Type C



USB Type-C Configuration Channel (CC)

1. Detect attach of USB ports
2. Resolve cable orientation and twist connections to establish USB data bus routing
3. Establish “host” and “device” roles between two attached ports
4. Discover and configure Vbus: USB Type-C Current modes or USB Power Delivery
5. Configure Vconn
6. Discover and configure optional Alternate and Accessory modes




Type C Interconnection

DFP to UFP Functional model




New Forces Present

Type C




A Low Profile, orientation independent, high data rate connection (40Gbs).

USB3.1




Universally accepted interface going to 10Gbs and beyond.

PD



Management of a power network and device modes through a one line communication channel


Alt Mode



Devices in a link can dynamically re-assign USB Type C pin functionality.

Type C Testing Challenge


Orientation Independence



Test time **DOUBLES**

Test Twice for USB3.1 /2.0


Alternate Mode



Test DisplayPort!

Type C Testing Challenge

- Power Management



CC1 /CC2

Vconn

Precedence	Mode of Operation	Nominal Voltage	Maximum Current
Highest	USB PD	Configurable	5 A
	USB Type-C Current @ 3.0 A	5 V	3.0 A
	USB Type-C Current @ 1.5 A	5 V	1.5 A
	USB BC 1.2	5 V	Up to 1.5 A
↓	Default USB Power	USB 3.1	5 V, 900 mA
		USB 2.0	5 V, 500 mA
Lowest			

- PROFILE 1
5V @ 2A
10W
Default
- PROFILE 2
5V @ 2A, 12V @ 1.5A
18W
- PROFILE 3
5V @ 2A, 12V @ 3A
36W
- PROFILE 4
5V @ 2A, 12V, 20V @ 3A
60W
Limit fo
- PROFILE 5
5V @ 2A, 12V, 20V @ 5A
100W
Limit fo

Power

Topics Today



- TYPE-C 接口技术

- TYPE-C 接口
- TYPE-C 技术
- Power Delivery 技术
- 问题和挑战


- TYPE-C 测试方案

- 发送端测试
- 接收端测试
- Cable/连接器测试
- Power Delivery测试


Keysight Type C Test Fixture





N7015A: High Speed Fixture



N7016A: Low Speed Fixture



Type C-USB3.1 Transmitter Test Solution




USB.1 Test Report

Overall Result: PASS



Test Configuration Details	
Device Description	
10GTransFunc	C:\Users\Public\Documents\Infinium\Apps\USB3Test\TransferFunctions\USB3Gen2ReferenceChannel.t4
6GTransFunc	C:\Users\Public\Documents\Infinium\Apps\USB3Test\TransferFunctions\USB3 TX Device Channel.t4
Input File Path	Device 1
Input Signal Type	Saved signal
AdcMode	AUTO
DC Gain	0
Reference Clock	SSC
De-emphasis Mode	-3.5 dB
Device	Device
Device ID:	Device 1
Test Session Detail	
Infinium SW Version	05.50.0005
Infinium Model Number	DSAV334A

Trial 1: Transition Eye Diagram

Type C-DisplayPort Transmitter Test Solution



Type C-USB3.1 Receiver Test Solution




Type C-Cable/Connector Compliance Test

New Solution

•**ALL** parameters can be measured with **ENA Option TDR**

One-box Solution !!



- ENA Mainframe
 - E5071C-4D5: 4-port, 300 kHz to 14 GHz
 - E5071C-4K5: 4-port, 300 kHz to 20 GHz
- Enhanced Time Domain Analysis Option (E5071C-TDR)
- ECal Module (N4433A)

(*) The list above includes the major equipment required. Please contact our local sales representative for configuration details.

Agilent 89610-10000 USB 3.0 Connector & Cable Assembly Compliance Test

Version 1.0


July 2009

Universal Serial Bus 3.0 Specification Version 1.0
Agilent Method of Implementation (MOI) for USB 3.0
Connectors and Cable Assemblies Compliance Tests
Using Agilent E5071C ENA Network Analyzer Option
TDR

MOI

(Method of Implementation)

Step-by-step procedure on how to measure the specified parameters in the specification document using ENA Option TDR.



Test Fixtures

Fixtures are available for purchase through Luxshare-ICT.

<http://web.luxshare-ict.com/en/>



ENA Option TDR is a authorized test tool for Cable PHY.


<http://www.vesa.org/displayport-developer/certified-components/>

Type C-Cable/Connector Compliance Test

Measurement Parameters (Normative & Informative)

Time Domain

Frequency Domain



Type C-Power Delivery Test Solutions

Power Delivery



S series Oscilloscope

GRL
GRANITE RIVER LABS

For Keysight Digital and Mixed Signal Oscilloscopes
USB Power Delivery Compliance Test Software (GRL-USB-PD)
and USB Type-C™ Test Controller (GRL-USB-PD-C1)

Quickly run USB Power Delivery(USB-PD) compliance and Validation Tests with any Keysight Windows Oscilloscope

Product Overview

GRL's USB Power Delivery (GRL-USB-PD) Compliance Test Software is the world's first oscilloscope based software tool designed for testing to the USB Power Delivery (USB-PD) specifications. GRL-USB-PD software, when used "stand-alone" on any Windows based oscilloscope, provides a simple and efficient way to perform USB-PD electrical parametric and protocol measurements. GRL-USB-PD provides waveform visibility and protocol analysis making it ideal for design and debug of USB Type-C Power Delivery floor and end products.

When used with GRL's USB Type-C Test Controller (GRL-USB-PD-C1), GRL-USB-PD provides a complete automated solution for Compliance Testing to the USB Power Delivery Compliance Plan.

GRL has been a contributor to the USB Power Delivery Specification and Compliance Working Groups since mid-2014. With GRL's USB-PD Compliance Solution, you can perform the required USB-PD Compliance tests in your own lab before attending a workshop or sending your device to a lab for Compliance.

KEYSIGHT TECHNOLOGIES

For most new designs using the USB Type-C Connector, the USB PD Specification provides the handshaking contract

GRL-USB-PD Power Delivery SW



N2873A passive probes




1147B current probe

GRL-USB-PD-C1

Rear Panel



Front Panel




N3301A /N3303A Electronic Load



N6700 Modular Power System



USB Type-C Device PD Test Setup



PD Test Contents

Test Name	Test Description	Required Tests by Device Type			
		Provider Only	Consumer Only	Dual Role Device	
				P/C	C/P
	Primary Power Delivery Device Tests				
	BMC PHYSICAL LAYER TESTS-TRANSMIT				
BMC-PHY-TX-EYE	BMC Transmitter Eye Diagram Test	✓	✓	✓	✓
BMC-PHY-TX-BIT	BMC Transmit Bit Rate and Bit Rate Drift	✓	✓	✓	✓
	BMC PHYSICAL LAYER TESTS-RECEIVE				
BMC-PHY-RX-BUSIDL	BMC Bus Idle Detection Test	✓	✓	✓	✓
BMC-PHY-RX-INT-REJ	BMC Receive Interference Rejection Test	✓	✓	✓	✓
	BMC PHYSICAL LAYER TESTS-MISCELLANEOUS				
BMC-PHY-TERM	BMC Termination Impedance Test	✓	✓	✓	✓
BMC-PHY-MSG	BMC PHY Level Message Test	✓	✓	✓	✓
	PROTOCOL SPECIFIC-Message Checks				
BMC-PROT-SEQ-GETCAPS	Get_Source_Cap and Get_Sink_Cap Test	✓	✓	✓	✓
BMC-PROT-SEQ-CHKCAB-P-PC	Check Cable Capabilities (3A Marked) Test	✓	✓	✓	✓
BMC-PROT-SEQ-CHKCAB-NOMRK-P-PC	Check Cable Capabilities (UnMarked) Test	✓	✓	✓	✓
BMC-PROT-SEQ-CHKCAB-CP-ACC	Check Cable Capabilities (3A Marked) Test-After PR Swap	✓	✓	✓	✓
BMC-PROT-SEQ-CHKCAB-NOMRK-CP-ACC	Check Cable Capabilities (UnMarked) Test-After PR Swap	✓	✓	✓	✓
BMC-PROT-SEQ-DRSWAP	Dual Role Swap Test	✓	✓	✓	✓
BMC-PROT-SEQ-VCSWAP	VCONN Swap Test	✓	✓	✓	✓
BMC-PROT-DISCOV	ID Checks	✓		✓	✓
BMC-PROT-SEQ-SWAP-REJ	Reject Swap Test - Provider/Consumer			✓	
BMC-PROT-BIST-NOT-5V-SRC	BIST Functionality at Above 5V Test	>5V DUT Only		>5V DUT Only	
BMC-PROT-REV-NUM	Revision Number Test	✓	✓	✓	✓
	Power Source/Sink Tests				
BMC-POW-SRC-LOAD-P-PC	Source Dynamic Load Test, Provider or Provider/Consumer	✓		✓	
BMC-POW-SRC-LOAD-CP-ACC	Source Dynamic Load Test, Consumer/Provider Accepting Swap				✓
BMC-POW-SRC-TRANS-P-PC	PDO Transition Test - Source, Provider or Provider/consumer	✓		✓	
BMC-POW-SRC-TRANS-CP-ACC	PDO Transition Test - Source, Consumer/Provider Accepting Swap				✓
BMC-POW-SNK-TRANS-C-CP	PDO Transition, Current Draw and Suspend Test-Sink, Consumer or Consumer/Provider		✓		✓
BMC-POW-SNK-TRANS-PC	PDO Transition, Current Draw, and Suspend Test, Sink, Provider/Consumer			✓	

Physical Layer Results

– BMC Eye & Measurements

Select Packet From List


When Checked, All Results Update On Selected Packet

Packets Info


Packets: Update Test details on packet select

Index	Port ...	Message	SOP	PDO	Message Type	M...	Header (MSB t...	Payload (MSB ...	CRC
0	DFP	Source Capabilities	SOP-Sync1 S...	Fixed Supply;Fixed Supply;Fixed ...	Data	0	0x31 0x61	0x6412C 0x...	0xC704DD7B
1	DFP	Source Capabilities	SOP-Sync1 S...	Fixed Supply;Fixed Supply;Fixed ...	Data	0	0x31 0x61	0x6412C 0x...	0xC704DD7B
2	DFP	Source Capabilities	SOP-Sync1 S...	Fixed Supply;Fixed Supply;Fixed ...	Data	0	0x31 0x61	0x6412C 0x...	0xC704DD7B
3	DFP	Source Capabilities	SOP-Sync1 S...	Fixed Supply;Fixed Supply;Fixed ...	Data	0	0x31 0x61	0x6412C 0x...	0xC704DD7B
4	UFP	Good CRC	SOP-Sync1 S...		Control	0	0x00 0x41		0xC704DD7B
5	UFP	Request	SOP-Sync1 S...	Request;	Data	0	0x10 0x42	0x3804B12C	0xC704DD7B

Pass/Fail BMC 'One'



Pass/Fail BMC 'Zero'



Pass/Fail Measurements


Test Results

Selected Packet Test Result:

Index	Test Name	Test Result	Test Limit	Average Value	Minimum Value	Maximum Value
1	Eye Diagram One Mask Test	PASS	-	-	-	-
2	Eye Diagram Zero Mask Test	PASS	-	-	-	-
3	CRC Test	PASS	-	-	-	-
4	Rise Time Test	PASS	X > 300 ns	577.890240 nS	306.714206 nS	50.0666786 µS
5	Fall Time Test	PASS	X > 300 ns	326.930994 nS	320.798611 nS	340.279018 nS
6	Symbol Encoding Test	PASS	-	-	-	-
7	Packet Format Test	PASS	-	-	-	-
8	Bit Rate Test	PASS	(270 < X < 330) Kbps	295.931 Kbps	292.997 Kbps	304.435 Kbps
9	Inter-Frame Gap Test	PASS	X > 25µs	102.639847 mS	102.639847 mS	102.639847 mS
10	Unit Interval Test	PASS	(3.03 < X < 3.70) µs	3.37928346 µS	3.28477273 µS	3.41300000 µS
11	Voltage Swing Test	FAIL	(1.05 < X < 1.20) V	0.589 V	0 V	1.14 V
12	pBitRate Test	PASS	X < 0.25 %	0.026 %	0.026 %	0.026 %

Keysight USB Type C Solutions

USB3.1



TX SW

U7243B
USB Compliance
Test Software

RX SW

N5990A-102
USB Compliance Test
Software
-302 Link training tools

TX HW

DSAV254A
Infiniium
Scope




RX HW



M8020A JBERT

DisplayPort Test



U7232D
DP Compliance
Test Software

N5990A-155
DP Compliance
Test Software

DSAV164A
Infiniium
Scope



M8020A JBERT

Thunderbolt Test



N6463B
Thunderbolt
Compliance
Test Software

N5990A-104
Thunderbolt
Compliance Test
Software

DSAV334A
Infiniium
Scope



M8020A JBERT

MHL Test




N6460B
MHL
Compliance Test
Software

N5990A-153
DP Compliance
Test Software

DSAV164A
Infiniium
Scope




M8190A ARB




2015 Nov. USB-IF Workshop Update

2015 USB-IF WORKSHOP EVENT


➤ USB 2.0 Test




➤ USB 3.1 Gen2 Test



➤ USB 3.1 TYPE -C Test



➤ USB Power Deliver Test



Thank You!



Unlocking Measurement Insights for 75 Years

官方微信：是德科技官方微信

