

通讯设备

导电高分子固态铝电容




SMD



导针型

- ◆ 低阻抗
- ◆ 高纹波
- ◆ 长寿命，最高可达20,000小时
- ◆ RoHS认证
- ◆ 应用：
 - 网络程控交换机
 - 服务器


液态铝电解电容



SMD



导针型



牛角型



插片型



螺丝型

- ◆ 低阻抗
- ◆ 高纹波
- ◆ 耐高温，最高温可达125 °C
- ◆ 长寿命，最高可达12,000小时
- ◆ RoHS认证

- ◆ 应用：
 - Cable Modem
 - ADSL网通产品
 - 电脑设备

产品规格

电容类型	型态	系列	工作电压(V)	电容量(μF)	适用温度(°C)	负荷寿命(hrs)	尺寸(DxL, mm)	AEC-Q200
导电高分子 固态铝电容	SMD	PH	2.5~50	10~2,200	-55~+105	20,000	6.3x6~10x12.5	
		PV	2.5~63	10~2,700	-55~+105	15,000	5x6~10x12.5	
		VA	2.5~25	22~2,700	-55~+105	2,000	5x6~10x12.5	
		VC	2.5~16	68~2,700	-55~+105	2,000	5x6~10x12.5	
		VH	35~100	12~220	-55~+105	2,000	6.3x6~10x12.5	
		VL	4~50	10~2,200	-55~+105	5,000	6.3x6~10x12.5	●
		VP	6.3~35	56~1,800	-55~+125	2,000	6.3x9.5~10x12.5	●
		VT	4~50	10~2,200	-55~+125	1,000	6.3x6~10x12.5	●
	导针型	PC	2.5~63	10~2,700	-55~+105	15,000	5x6~10x20	
		PL	2.5~50	10~2,200	-55~+105	20,000	6.3x6~10x12	
液态铝电解 电容	SMD	CD	6.3~100	1~1,500	-55~+105	2,000~3,000	4x5.4~10x10	●
		CDL	6.3~100	22~1,500	-55~+105	5,000	8x10~16x16.5	●
		CDS	6.3~50	22~2,200	-55~+105	2,000	4x6~10x10	●
		CG	10~63, 80~160	2.2~470	-55~+125, -40~+125	2,000~3,000	6.3x5.4~10x10	●
		CGL	16~50	33~330	-40~+125	3,000	8x10~10x10	●
		CGS	6.3~100	1~4,700	-55~+125	1,000~2,000	6.3x6~16x16.5	●
		CK	6.3~50	0.1~1,000	-55~+105	2,000	4x5.4~10x10	●
		CKL	6.3~50	22~1,100	-40~+105	5,000	8x10~10x10	●
		CLL	6.3~50	10~1,000	-25~+105	7,000~10,000	4x7~10x10	●
	导针型	HE	16~400, 450	6.8~220	-40~+105, -25~+105	10,000	10x16~18x40	
		HF	6.3~100	5.6~18,000	-40~+105	4,000~8,000	5x11~18x40	
		HFN	6.3~50, 63~100	5.6~18,000	-55~+105, -40~+105	4,000~8,000	5x11~18x40	●
		HGN	6.3~50, 63~100	6.8~18,000	-55~+105, -40~+105	4,000~10,000	5x11~18x40	●
		HH	16~400, 450	6.8~680	-40~+105, -25~+105	10,000~12,000	10x16~18x50	
		HU	10~100	0.47~330	-25~+105	10,000	5x12~8x12	
		HW	400~450	6.8~120	-25~+105	15,000~20,000	6.3x11~20x45	
		MF	6.3~400, 450	1~15,000	-40~+105, -25~+105	2,000~5,000	5x11~18x40	
		SE	6.3~250, 350~450	0.47~22,000	-40~+105, -25~+105	3,000~5,000	5x11~25x50	
		SEN	160~400	2.2~120	-25~+105	3,000~5,000	6.3x11~18x40	●
		SER	160~400, 450	22~470	-40~+105, -25~+105	5,000	10x16~20x40	
		SGN	6.3~50	22~6,800	-55~+105	2,000~5,000	5x11~16x26	●
	牛角型	LZ	10~250, 350~500	68~68,000	-40~+105, -25~+105	2,000	20x20~35x65	
		TZ	200~450	220~1,800	-25~+105	10,000	30x30~40x60	
	插片型	LG	16~250, 315~450	22~10,000	-40~+105, -25~+105	2,000	25x25~40x80	
	螺丝型	LP	16~250, 350~500	470~500,000	-40~+85, -25~+85	3,000	35x80~90x190	

Su'scon

www.su-scon.com
sales@su-scon.com.tw

冠坤电子企业股份有限公司 KUAN KUN ELECTRONIC ENTERPRISE CO., LTD

台北 | +886-2-8226-9699 | 台湾新北市23511中和区建八路2号5楼之3
东莞 | +86-769-8731-8000 | 中国广东省523648东莞市清溪镇银河工业区
苏州 | +86-512-6285-7850 | 苏州工业园区启月街288号紫金东方广场1商幢2-1008室

